

INSTRUCTION MANUAL



DISPENSER NEEDDLES / TAPPERED TIPS




Packing List

The following items are included:


Tapered Tips / Stainless Needles 10 unit





How to use

1. Replace the cap with the needle in the plunger housing.





Nozzles Range

STAINLESS STEEL NEEDLES



STYLE	Ref.	COLOR	SOLDER PASTE	GAUGE	ØID (mm)	ØID (in)	ØOD (mm)	ØOD (in)	LENGTH (mm)	LENGTH (in)	TOTAL LENGHT (mm)	TOTAL LENGHT (in)	QTY
Stainless Steel Needles	ND18S6	Green	Type 2	18	0.84	0.050	1.27	0.033	6.5	0.25	24	0.25	10
	ND20S6	Pink	Type 3	20	0.61	0.036	0.90	0.024	6.5	0.25	24	0.25	10
	ND21S6	Purple	Type 3	21	0.51	0.032	0.82	0.020	6.5	0.25	24	0.25	10
	ND22S6	Blue	Type 3	22	0.41	0.028	0.72	0.016	6.5	0.25	24	0.25	10
	ND23S6	Orange	Type 3	23	0.31	0.025	0.63	0.013	6.5	0.25	24	0.25	10
	ND25S6	Plan Red	Type 4	25	0.25	0.020	0.50	0.010	6.5	0.25	24	0.25	10
	ND27S6	Clear	Type 5	27	0.2	0.016	0.40	0.008	6.5	0.25	24	0.25	10
	ND30S6	Lavender	Type 6	30	0.15	0.012	0.31	0.006	6.5	0.25	24	0.25	10

TAPERED TIPS



STYLE	Ref.	COLOR	SOLDER PASTE	GAUGE	ØID (mm)	ØID (in)	ØOD (mm)	ØOD (in)	LENGHT (mm)	LENGTH (in)	TOTAL LENGHT (mm)	TOTAL LENGHT (in)	QTY
Tapered Tips	ND18P	Green	Type 2	18	0.84	0.033	1.27	0.050	-	-	32	1.26	10
	ND20P	Pink	Type 3	20	0.64	0.024	1.20	0.048	-	-	32	1.26	10
	ND22P	Blue	Type 3	22	0.41	0.016	0.72	0.028	-	-	32	1.26	10
	ND25P	Red	Type 4	25	0.25	0.010	0.50	0.020	-	-	32	1.26	10
	ND27P	Orange	Type 5	27	0.2	0.008	0.40	0.016	-	-	32	1.26	10

Specifications

- Weight:
- Dimensions:

2g (0,004 lb) 95x55x40mm (3.74x2.16x1.57 in)

Complies with CE standards



Warranty

JBC's 2 year warranty covers this equipment against all manufacturing defects, including the replacement of defective parts and labour.

Warranty does not cover product wear or misuse. In order for the warranty to be valid, equipment must be returned, postage paid, to the dealer where it was purchased.



This product should not be thrown in the garbage. In accordance with the European directive 2012/19/EU, electronic equipment at the end of its life must be collected and returned to an authorized recycling facility.



www.jbctools.com